0422	CHIA HSING SCRAMBLE	-
0423	Approved For-Retease 2900/05/04: CIA-RDP68B00320R000100020110-8	
0425	29-48N 121-10E PLUS 19.5	
Ø 4 26	29-45N 121-02E PLUS 19.5	
9427	29-34N 120-53E PLUS 19.5	
0430	29-26N 120-40E LU CHIAO SCRAMBLE	
0432	29-13N 120-33E PLUS 19	
0440	28-47N 119-58E PLUS 19	
0442	28-57N T19-23E PLUS 19	
0445	28-58N 118-59E PLUS 19	
0447	28-46N 118-55E PLUS 19	
9450	28-44N 118-4ØE PLUS 19	
0453	28-33N 118-28E	
0455	28-23N 118-21E Ø454 CHU HSIN T/O	
0457	28-12N 118-33E	
Ø458	27-58N 118-34E PLUS 17	
Ø5 Ø 1	27-50N 118-24E 0459 NAN CHANG T/O	
Ø5 Ø2	27-4@N 118-1@E	
Ø5 Ø3	27-41N 117-59E	
Ø5 Ø 6	27-30N 117-57E PLUS 15	
0508	27-53N 117-33E PLUS 16	
Ø5 12	28-07N 117-40E	
Ø5 1 4	28-26N 117-58E	
Ø5 1 6	28-37N 118-02E ABORT	
Ø521	28-26N 118-26E	
Ø5 2.3	28-18N 118-52E	
Ø524	28-16N 119-00E	
Ø527	28-00N 119-10E	
Ø529	27-12N 119-15E	
Ø531	27-30N 119-26E	
Ø534	27-23N 119-42E	
Ø536	27-07N 119-50E	
Ø538	26-58N 119-45E	
0542	26-38N 119-57E EXIT POINT	
Ø5 45	26-23N 120-24E	
TOPSE	C R E T	
BT		

	Approved For elec	ase 2000/05	/04 : CIA-RDP68 0320R00	00100020110-8 ~	
			1370	(C)	
TOPS	S E C R E T 260706	Z CITE	1378	(m)	25X1A
PR I OR IT	Y			67	25X1A
				دم: 	25X1A
. FO	LLOWING ARE CHICO	M PLOTS OF	MISSION :		25X1A
TIME (Z		ALT	REMARKS	949	14
9 g . 50° A0		48°86, 48°1 ou ou °4°2, 48°16,	25X1C	\wedge	
0259	23-00N 120-25E	57,500		Exclided from automatic	
Ø3 Ø2	22-37N 120-24E	62,500		Excluded from automod	
Ø3 <i>0</i> 6	23-00N 120-53E	62,500		Excluded from ding a from	
0314	23-52N 120-58E	65,900			
0323	25-ØIN 121-25E	65,900			
Ø325	25-10N 121-22E	69,000			
Ø326	25-26N 121-12E	70,000			
Ø 3 31	25-37N 121-05E				
Ø 3 33	26-02N 121-02E	69,500			
Ø336	26-18N 120-46E	N/A			
0339	26-40N 120-28E	N/A			
0340	26-41N 120-25E	N/A			
0341	26-44N 120-15E	69,000			
7 03 42	26- 58 N 120-20E	N/A			
Ø3 45	27-08N 120-17E	69,000			
Ø3 47	27-24N 120-18E	PLUS 20.7			
Ø 3 52	277 ØN 120-17E	N/A			
0355	28-00N 120-33E		Ø354 FU CHOW Ø355		
			LU CHIAO (MIG)		
ラ Ø358	28-24N 12Ø-				
0401	28-36N 121-22E				
Ø4Ø2	28-40N 121-45E	PLUS 21			
0406	28-54N 121-54E	PLUS 20.7			
0407	29-01N 122-03E	PLUS 20.9			
0410			NING PO (MIG) 33,000		
0411	29-24N 122-12E		,		
0413	29-30N 122-32E F	PLUS 20			
0415	29-54N 122-04E				
Ø419	29-50N 121-43E F	LUS 19.5			
Ø42Ø	Approved For Release	ase 2000/05 LUS 19.5	/04 : CIA-RDP68B00320R00	00100020110-8	